



**WHITACRE GREER**  
**CLAY PAVER DETAIL**  
 SAND BED ON CONCRETE BASE  
 WITH ASTM CONFORMANCE REQUIREMENTS

\* THICKNESS OF AGGREGATE BASE WILL VARY WITH SUB-GRADE CONDITIONS AND CLIMATE. COLDER CLIMATES MAY REQUIRE THICKER BASES.

GENERAL NOTES:

- INSTALLER MUST USE STRING LINES AND/OR CHALK LINES TO KEEP PAVER BOND LINES STRAIGHT
- CONSULT AN ENGINEER FOR HEAVY VEHICULAR APPLICATIONS
- FOR VEHICULAR USE BEST PRACTICES REQUIRE HERRINGBONE OR CHEVRON PATTERN
- COMMERCIAL VEHICULAR APPLICATIONS REQUIRE THICKER PAVING UNITS

\* DETAIL PROVIDES GENERAL INFORMATION DRAWN FROM INDUSTRY STANDARDS AND MAY NOT BE APPROPRIATE FOR ALL PAVING APPLICATIONS. CONSULT LOCAL ENGINEERS FOR DESIGN AND CONSTRUCTION INFORMATION APPROPRIATE FOR YOUR AREA

SHEET:	<b>DETAIL 2</b>
SCALE:	1 1/2" = 1'-0"
DATE:	__-__-__
PROJECT:	_____

**WHITACRE GREER CLAY PAVER DETAIL (2)**  
 ALLIANCE, OHIO

THE PAVER PLACE

**WHITACRE-GREER**  
Quality since 1900

DETAIL COMPLETED BY JOSHUA DAVID CUNNINGHAM ARCHITECT-CHICAGO, ILLINOIS 312.852.1220