

SAFETY DATA SHEET

Date Completed: November 18, 2014

Latest Revision: November 18, 2014



1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Material Name: Firebrick
Trade Name: Firebrick / Ladle brick / Low duty refractory
Chemical Family: Predominately Aluminum Silicates
Formula: Mixture

Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Intended Use: Residential fireplaces and stoves, Steel and Aluminum industry

Details of the Supplier of the Safety Data Sheet

Whitacre Greer Company
1400 S Mahoning Ave
Alliance, Ohio 44601
Product Support/Technical Services Phone: 1-800-947-2837

Contact E-Mail: info@wgpaver.com

2. HAZARDS IDENTIFICATION

Appearance: Granular brick-shaped solid; comes in buff and red

Hazard Classification of the Substance or Mixture: N/A

Signal Word: None.

Hazard Statement: Brick dust may contain crystalline silica, a chemical that has been determined by certain agencies to cause cancer. See Section 11 for more information on health hazards.

Pictograms: Not applicable.

Precautionary Statements: None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	% Weight
Aluminum Silicates	1344-28-1	50 – 85
Quartz	14808-60-7	Varies
Barium compounds	Various	0 – 3
Iron compounds	Various	0 –15

The above chemistries are provided for industrial hygiene and environmental purposes and are not intended to represent product specifications. This information has been compiled from data believed to be reliable. Elements such as aluminum, arsenic, boron, calcium, chromium, cobalt, copper, lead, molybdenum, nickel, tin, titanium, vanadium, and zirconium may be present in trace amounts. Pavers as shipped do not present an exposure hazard.

SAFETY DATA SHEET

Material Name: Firebrick

Page 2 of 5

Latest Revision: November 18, 2014

4. FIRST AID MEASURES

Description of First Aid Measures

Eye Contact: Flush with running water. Obtain medical assistance if irritation continues.
Skin Contact: Wash with soap and water. If an allergic reaction causes a rash that does not heal within a few days consult a physician.
Ingestion: None (no known acute effects).
Inhalation: Remove from exposure to airborne particulates. Consult a physician if breathing does not return to normal.
Medical Conditions Aggravated by Exposure: Excessive dust exposure may aggravate any existing respiratory disorders or diseases.

5. FIRE-FIGHTING MEASURES

Fire / Explosion Hazards: Bricks as shipped do not pose a fire or explosion hazard.

6. ACCIDENTAL RELEASE MEASURES

Cleanup Procedures: Bricks as shipped do not present a human or environmental hazard that requires special clean-up measures

7. HANDLING AND STORAGE

Precautions for Safe Handling: Minimize dust generation and accumulation. Avoid breathing dust. Always wet saw or vacuum. Provide adequate ventilation to maintain exposures below OSHA PEL and ACGIH TLV for quartz and other substances.

Conditions for Safe Storage: Always stack and store bricks in a stable manner to avoid falling hazards.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Table with 2 columns: Substance (Aluminum Silicates, Quartz, Iron Compounds) and Exposure Limits (OSHA PEL, ACGIH TLV). Values include 15 mg/m3, 10 mg/m3, and 10 / %SiO2 + 2 mg/m3 (respirable).

SAFETY DATA SHEET

Material Name: Firebrick

Page 3 of 5

Latest Revision: November 18, 2014

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Barium Compounds

OSHA PEL
ACGIH TLV

Not available
Not available

Exposure Controls

Engineering Controls:

Provide adequate ventilation to maintain exposures below the OSHA PEL and ACGIH TLV for quartz and other substances

Personal Protective Equipment:

Refer to applicable national standards and regulations in the selection and use of personal protective equipment (PPE).

Feet:

Use of steel toe shoes is recommended when handling brick.

Eyes and Face:

Face shields should be used when sawing brick.

Skin:

Use gloves and or protective clothing if abrasions or allergic reactions are experienced.

Respiratory protection:

For airborne concentration exceeding the OSHA PEL or ACGIH TLV use a NIOSH and/or MSHA approved respirator.

Other:

Use of wet sawing or vacuum methods is recommended anytime that bricks must be cut.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Granular solid

Color:

Buff or Red

Odor:

Essentially odorless

Odor Threshold:

No data available

Molecular Formula:

Mixture

Molecular Weight:

Mixture

Solvent Solubility:

No data available

Water Solubility:

Negligible

Boiling Point:

No data available

Melting Point:

1500 C

Specific Gravity:

2.7

Vapor Pressure (kPa):

No data available

Vapor Density (g/ml):

No data available

10. STABILITY AND REACTIVITY

Reactivity:

Bricks as shipped are stable and not reactive.

Latest Revision: November 18, 2014

11. TOXICOLOGICAL INFORMATION

Effects of Short Term and Long Term Exposure:

Short Term

Bricks as shipped do not present an inhalation, ingestion or contact hazard. However, operations such as sawing and grinding may result in the following effects:

Eye:	May cause irritation by abrasion with dust or chips.
Skin:	Brick dust or chips may cause allergic reactions in hypersensitive individuals; May cause cuts and skin abrasions.
Inhalation:	Brick dust or chips may cause congestion and irritation in nasal and respiratory passages.
Ingestion:	No known acute effects.

Long Term

Excessive exposures to respirable particulates (dust) over an extended period of time may result in the development of pulmonary diseases such as silicosis.

Information on Toxicological Effects

General Information:

Toxicological properties of the formulation have not been investigated. The information in this section describes the potential hazards of crystalline silica. Brick dust may contain crystalline silica, a chemical that has been determined by certain agencies to cause cancer and other chemicals known to cause cancer, birth defects and other reproductive harm. Inhalation of brick dust above established or recommended exposure levels should be avoided by use of wet sawing or shaping and/or use of a NIOSH approved respirator.

Carcinogen Status:

The following carcinogenicity classifications for crystalline silica have been established by the following agencies:

OSHA:	Not regulated as a carcinogen
IARC:	Group 1 carcinogenic in humans
NIOSH:	Carcinogen, with no further categorization
NTP:	Known carcinogen

12. ECOLOGICAL INFORMATION

There are no known environmental impacts.

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods:

Dispose of waste in accordance with all applicable laws and regulations. State specific and community specific provisions must be considered. It is recommended that waste minimization be practiced.

14. TRANSPORT INFORMATION

This material is not regulated for transportation as a hazardous material/dangerous good.

DOT: Bricks as shipped are not hazardous materials per DOT regulations.

Latest Revision: November 18, 2014

15. REGULATORY INFORMATION**Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture**

RCRA	Pavers in its solid form is typically considered a non-hazardous waste for disposal, but local regulation may vary, therefore all waste must be disposed, recycled, and reclaimed in accordance with federal, state, and local environmental control regulations. Water containing brick solids, such as from wet sawing operations, should also be disposed of in accordance with federal, state and local environmental regulation. Brick waste should not be used as a blasting agent.
EPCRA Section 311/312:	Bricks as shipped are not a Section 311/312 reportable product.
EPCRA Section 313:	Bricks as shipped are not subject to the Section 313, Toxic Chemical Release Inventory reporting requirements.
DOT:	Bricks as shipped are not hazardous materials per DOT regulations.

16. OTHER INFORMATION

Whitacre Greer considers our product an "article" as defined in 30 CFR 1200(b)(g)(iv) and 40 CFR 372.38. As an article, an SDS is not required and the product is exempt from all other requirements of the hazard communication standard. OSHA requires an SDS for brick because it is occasionally dry sawed. We recommend only wet sawing of brick.

This SDS was prepared with information believed accurate at the time of preparation and was prepared and provided in good faith. However, Whitacre Greer assumes no responsibility as to the accuracy or suitability of such information and no warranty expressed or implied is made